



SPIRAL WRAP

HIGH DENSITY POLYETHYLENE SPIRAL GUARD



Good UV
resistance



Highly flexible
Fatigue resistant



Good chemical
resistance



High impact
resistance



Manufactured
in Australia



Australian manufactured high density polyethylene spiral sheathing, designed for heavy duty flexible protection in a wide range of industrial applications. Suitable for applications requiring protection of cable, hydraulic hose, air and gas lines. Excellent durability, providing enhanced impact and abrasion resistance. Good chemical resistance, UV resistance, with a long fatigue life. Available in a FRAS formulation for applications requiring flame-retardant anti-static properties. Supplied in black, custom colours are available on request.

PROPERTIES

Minimum Continuous Operating Temperature	-50 °C
Maximum Continuous Operating Temperature	80 °C
Minimum Short Term Operating Temperature	-65 °C
Maximum Peak Operating Temperature	100 °C
Flammability UL94 (standard formulation)	HB Rating
Flammability UL94 (FRAS formulation)	V0 self-extinguishing
Weatherability	Good UV Stabilisation

PART NUMBERS DESCRIPTION

GP-SW16-20	16MM X 20MT SPIRAL WRAP
GP-SW20-20	20MM X 20MT SPIRAL WRAP
GP-SW25-20	25MM X 20MT SPIRAL WRAP
GP-SW32-20	32MM X 20MT SPIRAL WRAP
GP-SW40-20	40MM X 20MT SPIRAL WRAP
GP-SW50-20	50MM X 20MT SPIRAL WRAP
GP-SW60-20	60MM X 20MT SPIRAL WRAP

MANAGEMENT SYSTEMS



Manufactured in Australia under ISO9001:2015 certification. All information contained in this document is given in good faith but without warranty. All dimensions are nominal values. We reserve the right to make technical changes to this document without prior notice.

**GP TRUCK PRODUCTS AVAILABLE FROM
TRUCK & TRAILER PARTS OUTLETS AUSTRALIA WIDE.**



UNCOMPROMISING PERFORMANCE

Phone +61 3 95801811
sales@gptruckproducts.com.au
www.gptruckproducts.com.au